Airless Paint Sprayer FSG M4.0





Fedor-Schnorr-Straße 23 08523 Plauen

info@vep-baumaschinen.de www.v-e-p.net

Everything at a **glance!**

The **FSG M 4.0** airless paint sprayer is particularly suitable for smooth surfaces. A smooth spray product is achieved even on hard-to-reach areas, such as beams or corners.

Depending on the paint thickness to be applied, spraying pressure and distance of the surface to be processed, the spraying speed and also the spraying pressure can be optimally adjusted.

Basic equipment

- Spray gun
- High pressure hose
- Spray gun
- Extension lance 50 cm
- Nozzle set
- Filter
- Membrane
- Tool bag with key

Technical data

Power: 1500 Watt
Mains connection: 230 V/ 50 Hz
Spraying pressure: up to 220 bar
Flow rate: up to 4 l/ min

Weight

Machine: 29 kg

Application

For solvent-based or water-soluble coating materials such as:

- Emulsion and latex paints for external facades and internal walls
- Varnishes and paints, primers, PVC paints, undercoats, primers, fillers, rust protection paints
- Wood preservatives, oils, stains, disinfectants
- Also suitable for roof coating

Range of application

Painting works of any kind:

- on plastered and wallpapered walls
- doors
- vehicle parts
- garage doors
- wooden fences
- furniture
- garden houses
- terraces, etc.

