

Plastering Machine

VR6



V.E.P. BAUMASCHINEN GMBH

Fedor-Schnorr-Straße 23
08523 Plauen
GERMANY

info@vep-baumaschinen.de
www.v-e-p.net

Everything at a glance!

The **VR 6** plastering machine is suitable for all machine-compatible dry mortars. Depending on the requirements, it is possible bagged material or silo material by means of a commercially available conveyor system. The dry mortar is conveyed to the mixing pump via the inclined cellular wheel. In the mixing pump, the material is mixed under metered water supply and then conveyed through the mortar hose by a highly wear-resistant, extremely pressure-stable worm pump.

Basic equipment

- Mixing tube with interchangeable flange
- Pump motor with planetary gear
- Compressor
- Generously designed tool compartment
- Pressure cut-off 42V
- Water & electricity safety circuit
- Water Air Fitting compact
- Mortar hose 25 mm - 10 m
- Air hose 1/2" - 11m
- Sprayer 25 mm
- Screw pump (optional maintenance free/adjustable)
- Mortar pressure gauge LW 35
- Coupling reducer 35V 25V
- Cleaner shaft & mixer cleaner
- On-board tools, Operating Instructions

Technical data

- Drives: Pump motor: 400 V/ 50 Hz/ 5,5 kW / 400 rpm
Star wheel motor: 400 V/ 50 Hz/ 0,55 kW / 28 rpm
- Connection: 400 V/ 32 A
- Fuse protection: 3 x 25 A
- Water connection: 3/4" at least. 2,5 bar with machine running
- Delivery rate: 5-85 l/min depending on pump type 22l as standard
- Delivery distance: Hose diameter 25 mm max. 30 m
Hose diameter 35 mm max. 50 m
Floating screed up to 80 m
- Operating pressure: max. 30 bar
- Air compressor: 0,9 kW/ 0,25 Nm³/min



Weights

Complete machine:	272 kg
Compressor:	23 kg
Mixing pump:	92 kg
Basic body:	157 kg

Dimensions

Length:	1120 mm
Width:	730 mm
Height:	1500 mm
Filling height:	910 mm
Funnel content:	150 liters

The machine can be supplied for any voltage required. optionally also switchable