

Mortar Pump

VR4-400



V.E.P. BAUMASCHINEN GMBH

Fedor-Schnorr-Straße 23
08523 Plauen
GERMANY

info@vep-baumaschinen.de
www.v-e-p.net

Everything at a glance!

The **VR 4 - 400** is a plaster and mortar pump.

Many different materials can be processed, such as: Mortar, flowing screed, various plasters, adhesives, insulating plasters, gypsum-lime plasters, cement plasters and much more.



Basic equipment

- Eccentric screw pump 2L6 for 6-8 mm
- Mortar pressure gauge
- On-board tool kit
- Instruction manual

Technical data

	Pump VR 4 FU	mit Tellermischer
Drive:	Planetary gear motor 7,5 kW 400 Volt, 87 Hz	Getriebemotor 2,2 kW, 400 Volt, 50 Hz
Power connection:	400 Volt / 32 A	
Fuse protection:	25 A	
Material feed rate:	5-85 l/min, depending on the material, consistency and pump type	
Working pressure:	max. 25 bar	
Tank volume:	100 l	80 l
Weight:	187 kg	189 kg
Hopper height:	620 mm	1150 mm
Length:	2100 mm	
Width:	680 mm	
Height:	695 mm	1200 mm

Our advantages

- High flow rates over long distances
- Multi-purpose pump with and without mixer
- Robust construction
- Control via air or remote control
- Variable flow rates, adjustable by potentiometer

**The machine can be supplied for any voltage required.
optionally also switchable**